



95 Floor Finish Strip

by Chem-Coat Industries, Inc. Product Code: S-95

95 FLOOR FINISH STRIP is specially formulated for use in automatic floor scrubbing machines. To remove old wax or finish, first sweep the floor with a brush or dust mop. Use 1 part stripper to 15 parts water (9 oz. 95 FLOOR FINISH STRIP per gallon of water). Apply with a mop or floor machine. For faster removal of wax or finish, use floor machine and abrasive pad.

If areas under desk and along walls have multiple coats of finish, use a solution of 1 part 95 FLOOR FINISH STRIP to 3 parts water. Avoid splashing solution on painted baseboards or walls. Pick up soiled scrubbing solution with a mop or wet vacuum. Rinse floor thoroughly before rewaxing.

95 FLOOR FINISH STRIP removes hardened floor waxes and built-up layers of water-resistant floor finishes. It is NOT a, general purpose floor cleaner. Strong concentration on un-waxed floors may cause discoloration. Avoid splashing cleaning solution on painted surfaces as spotting may occur.

Before cleaning, place warning signs in regards to wet floor around work area. Always place warning signs when cleaning the floors. Do not remove the signs until the floor is completely dry and safe to walk on.

Do a small test area before project starts to assure compatibility of all products, an approval. KEEP OUT OF REACH OF CHILDREN AND PETS

Do not mix or use with any cleaners or household products. Always do a spot check before using on any surface.

WARRANTY

Chem-Coat Industries (CCI) warrants that at the time and place we make shipment, our material will be of good quality and will conform without published specifications in force on the date of acceptance of the order. **DISCLAIMER:** The information contained herein is included for illustrative purposes only and, to the best of our knowledge, is accurate and reliable. CCI cannot, however, under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As CCI has no control over the use to which others may put its products, it is recommended that the products be tested to determine if suitable for specific application and /or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine suitable products for specific application and assume all responsibilities in connection therewith.

in connection therewith.

Availability

1-Gallon Units, 5-Gallon Units, 55-Gallon Units

For product questions and availability, please contact: TEL: 972-485-8648, 1-800-511-2769 FAX: 972-485-0339 www.chem-coat.com or www.floordeluxe.com